

INDEX

- Accumulation (ACC), 68, 84
- Additive scaling parameter, 15
- Aggregation, 26, 28
- Agricultural indicator, 113–114, 118
- Agricultural lands, 183
- American Standard Code for Information Interchange format (ASCII format), 40, 156
- Anak Galas river, 183
- Ant colony algorithm, 88
- ArcGIS Server platform, 35–36, 38
- Artificial neural networks (ANNs), 88, 143 (*see also* Cuckoo search optimisation neural network (CSONN))
- Backpropagation (BP), 88
- Below detection limit (BDL), 180
- Best Management Practices (BMPs), 55
- Beta function, 29
- Bias correction method, evaluation of, 71
- Big data (*see also* Hydrological big data)
 - approach, 142
 - global case studies on big data applications in water resource engineering, 142–146
 - limitations and disadvantages, 146
 - potential of big data applications for managing water resources in Malaysia, 144–146
 - theoretical considerations, 144
- Black box model, 88
- Board of directors (BOD), 114
- Bukit Matuh (BM), 92
- Campus university, 130
- Chemical pollution, 174
- Chiku sub-catchment, 183
- Climate analytics-as-a-service (CAaaS), 143
- Climate change, 66
 - data collection, 67–68
 - methodology, 66–70
 - result, 71–75
 - RRI model, 69–71
 - statistical bias correction method, 68–69
 - study area, 66–67
- Climate data, 142
- Coefficient of correlation, 93
- Coefficient of efficiency, 93
- Communal irrigation systems (CIS), 113
- Composite indicator, 26, 28
- Contamination, 152
- Control system, 78
- Copula models, 46
- Cost analysis, 127, 129–130
- Cropping intensity (CI), 114–115
 - for CISs, 121
 - for Padada RIS, 122
- Cuckoo search algorithm (CS algorithm), 88–90
- Cuckoo search optimisation algorithm (CSO algorithm), 88–89
- Cuckoo search optimisation neural network (CSONN), 89–91
 - CSONND1 model, 93
 - CSONND2 model, 93

- CSOONND3 model, 93
- CSOONND4 model, 93
- CSOONND5 model, 93
- methodology, 92–94
- results, 94–96
- study area, 91–92
- Cuculus canorus*, 89
- Cumulative distribution functions (CDFs), 68
- Cut-off points, 29
- Dam, 34
 - break, 34, 39–40
 - failure and impact, 34–35
 - GIS application in dam break study, 35–36
 - methodology, 36–40
 - research procedure and data collection, 37–38
 - results, 40–42
- Damage factor, 15–16
- Damage to physical assets (DPA), 34
 - risk classification for, 40
- Data
 - analysis, 143
 - procurement, 142
 - standardisation, 144–145
- Deep big networks (DBNs), 143
- Delineation of risk zones, 41
- Department of Irrigation and Drainage (DID), 14–15, 67, 70
 - depth–damage relationships, 15
 - multiple regression function, 18
- Department of Statistics Malaysia (DOSM), 142
- Department of Survey and Mapping Malaysia (JUPEM), 6
- Depth–damage equation, 18
- Depth–damage function, 20
- Depth–damage relationship, 14–15, 17
- Differential evolution (DE), 88
- Digital elevation model (DEM), 68, 70, 144
- Digital image processing technique (DIPT), 163
- Digital terrain model (DTM), 101
- Direction (DIR), 68
- Discrete flow data, 48
- Discriminant function analysis (DFA), 176, 180–181
- Double-porosity media, 152–153, 162–163
- Drain bed slope, 55–57
- Drain flow depth, 58–59
- Drain maintenance, 78
- Drain spacing, 56–57
- Drain-widening projects, 78
- Drought-tolerant maize varieties (DT maize varieties), 143
- Earthquake vibration, 152
- Economic indicator, 114
- Equal weighting method, 28
- Expected annual damage (EAD), 16, 21
- Exposure, 26
- Exposure index (EI), 28
- Faulty or missing data, detection and restoration of, 145
- Field offices/IAs, interview with, 114
- Financial stability, 117
- First flush device, 126
- Flash floods, 54
- Flood Hazard Map, 41
- Flood hydrograph, 46
 - results, 48–51
 - smoothing functional data, 46–48
 - visualisation and outlier identification, 48
- Flood vulnerability, 26
 - classification, 30
 - decomposition, 30
 - indicators, 27
 - methodology, 26–29
 - results, 29–30
- Flood vulnerability index (FVI), 26, 28
- Flood(ing), 4, 14
 - arrival time, 35
 - depth, 15, 17, 35

- duration, 15
- duration, 35
- hazard, 5
- hazard to price valuation model, 6–7
- literature review, 4–5
- in Malaysia, 4–5
- methodology, 5–6
- risk assessment, 14, 16–17, 40
- velocity, 35
- Floodplain, 105, 107
 - effect, 100
 - impact, 4
 - information, 101
- Flow control structure, 78–79, 84
- Flow rate distribution, 57–58
- Flow regulator gate, 78–79
- Flush wave, 78
- Flushing device, 78
- Flushing gate, 78–79
- Functional data analysis (FDA), 46
- Functional hydrograph, 48
- Functional outliers, 51
- Functional principal component analysis (FPCA), 47
- Functional relationship, 26
- Functionality status, 114, 116–117

- Galas catchment system, 175–177
- Garden watering, water demand for, 127
- General circulation model (GCM), 66, 68, 71
- Generalised extreme value (GEV), 16–17, 20, 68
- Genetic algorithm (GA), 88
- Genetic programming (GP), 144
- Geographical information system (GIS), 142
 - application in dam break study, 35–36
 - modelling, 35–36
- Global Forest Watch (GFW), 183
- Global warming, 66
- Gouhou dam, 35

- ‘Grid overlay’ method, 35
- Groundwater, 152–154, 162
 - contamination, 152
 - flow, 88
 - groundwater-surface traces, 35
 - pollution, 152, 162

- Hazard, 5, 14, 16
- HAZUS-MH flood model, 36
- Heaviside function, 89
- Hedonic function, 6
- Hidden neurons (HNs), 90
- High-density rainbow box plot (HDR), 48, 50
- Houses, 4–5, 8, 15
- Hue saturation intensity (HSI), 156, 165
- Hydrass gate, 78
- Hydrocarbons, 152
- Hydrodynamic approach, 100
- Hydrodynamic models, 35
- Hydrological big data
 - integration of hydrological big data with GIS and remote sensing, 143–144
 - sharing platforms, 142–143
- Hydrological data, 142, 145
- Hydrological model integration, 144–145
- Hydrological simulation, 71–75
- HydroSHEDS, 68

- Image analysis processing method, 153
- Infiltrated sustainable urban drainage system, 55
 - methodology, 55–56
 - results, 56–60
- Infiltration, 54–56
- Information of Technology (IoT), 141
- Intact double-porosity, 154, 158
- Interferometric Synthetic Aperture Radar (IFSAR), 101
- Irrigation Management Office (IMO), 113

- Irrigation management transfer (IMT), 112
 - methodology, 113–114
 - results, 114–117
 - study area, 113
- Irrigation service fee performance (ISF), 114
- Irrigators associations (IAs), 113
- Joint bivariate distributions, 46
- Kampung Tunku, 79–81
- Kaolin soil, 153
- Kelantan River, 17
- Kruskal–Wallis H test, 177
- Landscape data, 142
- Landslide Hazard Zonation map (LHZ map), 35–36
- Langat River Basin, 66–68, 71
- Langat River flood area, 5–7
- Large catchment, 101
- Laterite soil properties, 165
- Learning rate (LR), 92
- Levenberg–Marquardt (LM), 88
- Lévy flights, 88–90
- Light non-aqueous phase liquid penetrations (LNAPL penetrations), 163 (*see also* Non-aqueous phase liquids (NAPLs))
 - materials and methods, 163–165
 - results, 165–169
- Linear programming and dynamic programming (LP-DP), 142
- Linear regression function, 17
- Local government units (LGUs), 117
- Local random walk, 89
- Machine learning (ML), 144
- Malaysia, 142–143
 - floods in, 5
 - Malaysia-led flood damage assessment, 14
- Manual Saliran Mesra Alam (MSMA), 78
- Market, 6, 11, 55
- Mass-balance approach, 127
- Mean curve, 47
- Median, 47
- Metaheuristic algorithm, 88
- Micro-scale flood risk assessment
 - case study area, 17
 - methodology, 15–17
 - results, 17–21
- Minimum night flow (MNF), 135, 137
- Min–max normalisation, 26
- Mode, 47
- Monthly average yield per hectare, 114–116
- Multidimensional risk, 31
- Multilayer perception-whale algorithm model (MLP-WA model), 144
- Multivariate techniques, 46
- Nash–Sutcliffe efficiency (NSE), 71, 73
- National Irrigation Administration (NIA), 113, 117
- National irrigation systems, 113
- National Property Information Centre (NAPIC), 6
- Neural networks (NNs), 89
- Ninth Malaysian Plan, 134
- Non-aqueous phase liquids (NAPLs), 152
 - materials and methods, 153–156
 - migration, 154–156
 - results, 156–159
- Non-point sources, 162
 - material and methods, 175–177
 - results, 177–183
- Non-revenue water (NRW), 134
- Normalisation, 26–28
- North-east monsoon (NEM), 67
- Objective weighting method, 28
- On-Site Detention (OSD), 55
- One-dimensional (1D), 101
 - modelling techniques, 101
 - stage–discharge relationship, 17

- Open storm water system, 78
- Organic contaminants, 162
- Outlier detection methods, 50
- Outlier identification, 48

- Padada RIS, 113–114, 122–123
- Particle swarm optimisation (PSO), 88
- Pattern, 163, 165
- Payback period, 127
- Penetration, 163–166
- Per cent bias (PBIAS), 71
- Performance evaluation, 112
- Pergau river, 182
- Philippine Crop Insurance Corporation (PCIC), 117
- Point sources, 162
- Post-storm flash floods, 55
- Precipitation, 88
- Price, 4–5
- Price valuation model, flood hazard to, 6–7
- PrimeLog+, 135
- PrimeWorks®, 135
- Probability weighted damage (PWD), 21
- Probable maximum floods (PMFs), 35
- Property
 - industry, 4
 - investment decision-making process, 4
 - price, 3

- Quantification of possible water harvested, 126
- Quantile Mapping, 68

- R studio programming software, 17
- Radial basis function (RBF), 144
- Rainbow plot, 48
- Rainfall, 88
 - rainfall–runoff model, 103
- Rainfall–runoff inundation model (RRI model), 66, 69–71
- Rainfall–runoff inundation-command user interface (RRI-CUI), 69

- Rainfall–runoff inundation-graphical user interface (RRI-GUI), 69
- Rainwater harvesting system (RWHS), 126
 - cost analysis, 129–130
 - design, 126–127
 - performance, 127
 - preliminary analysis, 127–128
 - results, 127–130
 - secondary analysis, 128–129
 - study area, 126
- Real-time clock module (RTC module), 78
- Realistic flood and drought forecasting and management, 145
- Red-green-blue (RGB), 156, 165
- Reliability, 127
- Reservoir, 34
- Resilience, 26
- Resilience index (RI), 28
- Review, 36, 142
- Risk, 16
 - assessment and classification, 41
 - classification for DPA, 40
 - flood, 84
- River flows, 46
- River Irrigation System (RIS), 112
- Root mean square error (RMSE), 71, 73
- Runoff, 78–79, 88
- Rural/urban strata, 15

- Scaled conjugate gradient (SCG), 88
- Scan electron microscopy (SEM), 165
- Sediment fingerprinting findings, 177–183
- Sediment source fingerprinting approach, 174–175
- Semuja Nonok (SN), 92
- Sg Lebir river system, 101
- Sg Relai river system, 101
- Shuttle Radar Topography Mission (SRTM), 68
- Simulated annealing (SA), 88
- Sluice gate, 78

- Smoothing functional data, 46–48
- Soaking process of water, 54
- Social indicator, 114
- Sources, 162
- South-west monsoon (SWM), 67
- Spatial data, 142
- Stage–damage relationship, 14, 16
- Statistical beta distribution, 28
- Statistical bias correction method, 68–69
- Storm water control, 54
- Storm water management model (SWMM), 80
 - flow control structure and flushing gate, 78–79
 - methodology, 80–82
 - rationale of study, 79–80
 - results, 82–84
- Streamflow
 - data, 46
 - stations, 67
- Sultan Abu Bakar Dam (SAB Dam), 34
- Sungai Bedup Basin, 91–92
- Sungai Busit (SB), 92
- Sungai Merang (SM), 92
- Sungai Teb (ST), 92
- Surfer Software, 165
- Susceptibility, 26
- Susceptibility index (SI), 28
- Sustainable Urban Drainage System (SUDS), 55
- Synthetic flood damage curves, 14
- Tabu search, 88
- Tenaga Nasional Berhad (TNB), 37
- Teton Dam, 34–35
- Three-dimensional diagram (3D diagram), 153
- Time of concentration, 100
 - data collection, 101–102
 - formulas, 100
 - methodology, 101
 - modelling processes, 103–104
 - rainfall, 105
 - results, 105–107
 - software selection, 101
 - study area, 101
 - sub-catchment, 105
- Tipping flushing gate, 78–79
- Toilet flushing, water demand for, 126
- Total Landslide Susceptibility Index, 36
- Trace elements, 177
- Transfer functions, 17, 68
- Trend analysis, 66
- Two-dimensional modelling
 - techniques (2D modelling techniques), 101
- Ultrasonic sensor, 78
- Universiti Kebangsaan Malaysia (UKM), 134
 - water consumption data collection, 135
 - water consumption data interpretation, 135–138
- Universiti Teknologi Malaysia (UTM), 55
- University of Nottingham Malaysia, 126
- Unmanned aerial vehicle (UAV), 37
- Urban Storm Water Management Manual (MSMA), 55
- Vacuum flushing, 78
- Vajont Dam, 34–35
- Value, 4, 9, 15, 26, 71, 144
- Varimax rotation, 48
- Velocity profiles, 59
- Vibration, 152–154, 163
- Visualisation, 48
- Volume, velocity, variety, value, veracity (5Vs), 144
- Vulnerability, 14, 26–27
 - curve, 14–15
 - relative classification, 28–29
- Water, 134
 - balance simulation, 127
 - loss in distribution networks, 134
 - metre, 135

- resource engineering, global
 - case studies on big data
 - applications in, 142–146
- scarcity, 134
- security, 135
- supply, 135
- Water consumption
 - data collection, 135
 - data interpretation, 135–138
- Water demand
 - for garden watering, 127
 - for toilet flushing, 126
- Water distribution system (WDS), 143
- Wave propagation, 101
- Weighted probability damage, 16
- Weighting, 28
- Whale algorithm model (WA model),
144
- World Health Organization (WHO), 135
- X-ray fluorescence (XRF), 176
- Yield after spillage (YAS), 127
- Yield before spillage (YBS), 127